




Abbreviations used on this Safety Data Sheet:

N/av. = Not available, N/ap. = Not applicable, ppm = parts per million, TLV = Threshold Limit Value.

NFPA Hazard Rating: 4-Extreme, 3-High, 2-Moderate, 1-Slight, 0-None, X-Blank

SECTION I - IDENTIFICATION OF THE MATERIAL AND SUPPLIER	
PRODUCT NAME	Activated Poultry Sense
OTHER NAMES	
MATERIAL USE:	Animal Litter Amendment, Odour Control
MANUFACTURER'S NAME	Absorbent Products Ltd
STREET ADDRESS	724 East Sarcee St.
CITY/PROVINCE	Kamloops, BC
POSTAL CODE	V2H 1E7
EMERGENCY TELEPHONE NUMBER:	1-800-667-0336
 <p>4 - extreme 3 - high 2 - moderate 1 - slight 0 - insignificant</p> <p><b>NFPA HAZARD RATING:</b> Health - 2, Flammability - 0, Reactivity - 1</p>	
 	

**SECTION II - HAZARD IDENTIFICATION**

This product is labelled in accordance with regulations administered by the Consumer Product Safety Commission. The typical use pattern and exposure in the workplace is generally not the same as what is experienced by consumers. The requirements of the Globally Harmonized System of Classification and Labelling of Chemicals applicable to this SDS differ from the labelling requirements of the Consumer Product Safety Commission and, as a result, this SDS may contain additional health hazard information not pertinent to consumer use and not found on the consumer product label.

**GHS Classification Substance or Mixture**

Carcinogenicity	Category 1A - H350i
Specific Target Organ Toxicity - (Repeated Exposure)	Category 1 - H372
Eye Irritant	Category 2A

**Label Elements:**

Hazard Pictogram



**Signal Word:** Danger

**Hazard Statements:**

H319 - Causes serious eye irritation

H350i - May cause cancer by inhalation.

H372 - May cause damage to organs through prolonged or repeated exposure if inhaled.

**Precautionary Statements:**

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash face, hands and any exposed skin thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P314 - Get medical attention/advice if you feel unwell.

P337+P313 - IF eye irritation persists: Get medical advice/attention.

P405 - Store in a safe, secure location.

P501 - Dispose of contents/container in accordance with local regulations.

**SUMMARY:** Prolonged and repeated exposure to excessive concentrations of this product's dust containing respirable size ( $\leq 10 \mu$ ) quartz, or any nuisance dust, can cause chronic pulmonary disease. Dust contact with eyes may cause temporary scratchiness or redness. Long term exposure can cause silicosis. The NTP (National Toxicology Program) and IARC (International Agency for Research on Cancer) has determined that crystalline silica inhaled from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure. **A single exposure under normal conditions will not result in serious adverse effects.** Citric acid has been classified as an eye irritant. It is considered harmful when in contact with eyes, causing serious irritation. It may be harmful if inhaled, causing respiratory tract irritation. Do not ingest. See section 8 (VIII) for personal protective equipment recommendations.

**MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED:** Pre-existing upper respiratory and lung disease, such as, but not limited to: Bronchitis, emphysema, and asthma.

**TARGET ORGAN(S):** Lungs, Eyes.

See SECTION XI - TOXICOLOGICAL INFORMATION

SECTION III - COMPOSITION OF SUBSTANCE				
HAZARDOUS INGREDIENTS	%	CAS NUMBER	OSHA PEL (ACGIH TLV)	LD50/ /LC 50 SPECIES AND ROUTE
Natural Zeolite	Up to 61%	1318-02-1	See Section VIII	N/av.
Free Crystalline Silica quartz	<3%	14808-60-7	See Section VIII	N/av.
cristobalite	<13%	14464-46-1		
(Occurs naturally in Zeolite)				
Citric Acid	39%	5949-29-1	See Section VIII	LD50 oral Rat = 11,700mg/kg LD50 intraperitoneal Rat = 885mg/kg LD50 oral Mouse = 5,040mg/kg LD50 intraperitoneal Mouse = 961mg/kg
<b>For sampling silica dusts refer to NIOSH Analytical Method 7500 or OSHA method ID 142</b>				
SECTION IV - FIRST AID MEASURES				
<b>Inhalation:</b>	Remove victim to fresh air. If breathing has stopped, a trained person should perform artificial respiration. Acute inhalation can cause dryness of the nasal passages and congestion of the upper respiratory tract.			
<b>Ingestion:</b>	Do not induce vomiting. Drink generous amounts of water to reduce bulk and drying effects. Never give anything by mouth to an unconscious person. Consult a physician.			
<b>Eyes:</b>	Wash with large quantities of water. Consult physician if irritation persists. May cause irritation/inflammation.			
<b>Skin:</b>	May cause dryness. Remove contaminated clothing. Wash with soap and water until clean. Use moisture renewing lotions if dryness persists.			
SECTION V - FIREFIGHTING MEASURES				
Flammability	No	Means of Extinction	Use Water Spray, alcohol-resistant foam, dry chemicals, and/or carbon dioxide	
Flashpoint (Method)	N/av.	Special Procedures	Non Flammable or Combustible under normal conditions.	
Auto ignition temperature	N/av.	Sensitivity to Impact	N/av.	
Hazardous Combustion Products	Carbon Oxides	Sensitivity to Static Discharge	N/av.	
Upper Flammability Limit (% by Volume)	N/av.			
Lower Flammability Limit (% by Volume)	N/av.			
SECTION VI - ACCIDENTAL RELEASE MEASURES				
<b>PROCEDURE FOR SPILLS / LEAKS:</b>	Avoid creating further dust. Vacuum with equipment fitted with a filter. Alternatively, wet sweep or wash away. Dispose of in accordance with local, State, and Federal Regulations.			
SECTION VII - HANDLING AND STORAGE				
<b>HANDLING PROCEDURES</b>				
Avoid creating dust. Repair or properly dispose of broken bags. Use enclosed handling.				
<b>STORAGE REQUIREMENTS</b>				
Store in a dry, well ventilated place to maintain quality. Keep containers closed and in good condition. Repair damaged containers.				
SECTION VIII - EXPOSURE CONTROLS AND PERSONAL PROTECTION				
<b>PERMISSIBLE EXPOSURE LIMITS:</b>	<b>OSHA PEL</b>	<b>ACGIH</b>	<b>OHS</b>	<b>OHS STEL</b>
(for airborne, nuisance dusts)	8 hr TWA	TLV	8 hr TWA	
Zeolite				
Total dust	15 mg/m <sup>3</sup>	Not detected	4 mg/m <sup>3</sup>	n/a
Respirable dust	5 mg/m <sup>3</sup>	Not detected	1.5 mg/m <sup>3</sup>	n/a
Crystalline quartz, cristobalite (respirable)	0.05 mg/m <sup>3</sup>	0.025mg/m <sup>3</sup>	0.025mg/m <sup>3</sup>	n/a
Citric Acid	None Listed	None Listed	None Listed	n/a
<b>EFFECTS OF CHRONIC EXPOSURE TO PRODUCT.</b> Exposure to quantities of crystalline silica respirable dust ( $\leq 10 \mu$ ), in the forms of quartz, cristobalite or tridymite, may occur when in the presence of airborne dust. If the dust concentration levels are in excess of the OSHA Permissible Limit (PEL-TWA 8hrs) of 0.05mg/m <sup>3</sup> or the ACGIH Threshold Limit Value (TLV) of 0.025mg/m <sup>3</sup> , the crystalline silica present is a known cause of silicosis, a progressive, sometimes fatal, lung disease. From the International Agency for Research on Cancer (IARC), a 2012 review of "Silica Dust, Crystalline, in the form of Quartz or Cristobalite" coded Monograph 100C concluded that Crystalline silica in the form of quartz or cristobalite dust is carcinogenic to humans (Group 1).				
<b>ENGINEERING CONTROLS (SPECIFY, E.G. VENTILATION, ENCLOSED PROCESS)</b>				
Control within recommended TLV/PEL, mechanical filtration to minimize dust. Refer to ACGIH publication "Industrial Ventilation" or similar publications for design of ventilation systems.				

<b>PERSONAL PROTECTIVE EQUIPMENT</b>			
<b>GLOVES</b>	Handle with Nitrile gloves. (0.11mm thickness, 480 min breakthrough time)		
<b>EYE</b>	Safety glasses with side-shields.		
<b>FOOTWEAR</b>	As required on jobsite.		
<b>CLOTHING</b>	Wear coveralls in high dust conditions.		
<b>RESPIRATOR</b>	Avoid breathing dust. See instructions below		
Bureau of Mines or NIOSH approved respirators for protection against pneumoconiosis producing dusts recommended when dust is present. If the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL) use quarter or half mask respirator (N95) with replacement dust filter or single use dust respirator with valve. If dust concentration is greater than ten (10) times and less than one hundred (100) times the PEL use full faceplate respirator with replaceable dust filter (N95 filter); if greater than one hundred (100) and less than two hundred (200) times the PEL use power air purifying (positive pressure) respirator with replaceable filter (N95 filters); if greater than two hundred (200) times the PEL use type C, automatic-air respirator, continuous flow type (positive pressure), with full facepiece, head or helmet.			
<b>SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES</b>			
<b>PHYSICAL STATE</b>	solid	<b>ODOR AND APPEARANCE</b>	Mild tangy odor, Brown granular
<b>VAPOR PRESSURE (mm Hg)</b>	N/ap.	<b>DENSITY (20 degrees Celsius)</b>	35lb/cu. ft. +/- 5
<b>VAPOR DENSITY (Air = 1)</b>	N/ap.	<b>SOLUBILITY IN WATER</b>	Insoluble, forms
<b>SPECIFIC GRAVITY (Water=1)</b>	2.1		colloidal suspension
<b>FREEZING POINT</b>	N/ap.	<b>pH</b>	1.7 - 2.2
<b>BOILING POINT</b>	N/ap.	<b>EVAPORATION RATE</b>	N/ap.
<b>SECTION X - STABILITY AND REACTIVITY</b>			
<b>CHEMICAL STABILITY (IF NO, UNDER WHICH CONDITIONS)</b>	YES	X	
	NO		
<b>INCOMPATIBILITY WITH OTHER SUBSTANCES (IF YES, SPECIFY)</b>	YES	X Hydrofluoric acid, oxidizing & reducing agents, bases, nitrates	
	NO		
<b>REACTIVITY, AND UNDER WHAT CONDITIONS</b>	N/ap.		
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b>	Under fire conditions - Carbon Oxides		
<b>CONDITIONS TO AVOID</b>	None in Designed Use		
<b>SECTION XI - TOXICOLOGICAL INFORMATION</b>			
<b>PRIMARY ENTRY ROUTE(S):</b>			
<b>Eyes:</b>	Can cause irritation or inflammation.		
<b>Skin:</b>	May cause dryness and allergic reactions with continued exposure.		
<b>Ingestion:</b>	May be harmful if swallowed.		
<b>Inhalation:</b>	Persistent dry cough, throat irritation and labored breathing on exertion are symptomatic of exposure to airborne dust. Exposure may aggravate existing upper respiratory tract diseases such as asthma, bronchitis or emphysema. Acute (short term) exposure to dust levels exceeding the PEL may cause irritation of respiratory tract resulting in a dry cough. Eyes may develop redness and become itchy. Chronic (long term) exposure to crystalline silica contained by airborne diatomaceous earth, where levels are higher than TLV's, may lead to the development of silicosis, other respiratory problems, or some forms of cancer. From the International Agency for Research on Cancer (IARC), in a 2012 review of SILICA DUST, CRYSTALLINE, IN THE FORM OF QUARTZ OR CRISTOBALITE (monograph 100C) concluded that "Crystalline Silica in the form of quartz or cristobalite dust is carcinogenic to humans (group 1)." The NTP (National Toxicology Program) has determined that "Respirable crystalline silica, primarily quartz dust occurring in industrial and occupational settings, is know to be a human carcinogen."		
<b>SECTION XII - ECOLOGICAL INFORMATION</b>			
No data available on persistence, degradability, bioaccumulation, soil mobility, or other adverse affects. Used product that has become contaminated may have significantly different characteristics than uncontaminated product, and should be re-evaluated accordingly. Dispose of in accordance with Local, State, and Federal regulations.			
<b>SECTION XIII - DISPOSAL CONSIDERATIONS</b>			
Uncontaminated waste is not hazardous as defined by the Resource Conservation and Recovery Act (RCRA, 40 CFR261). Contaminated waste must be evaluated based on contamination source. Consult local agencies as needed. Dispose of in accordance with Local, State, and Federal regulations.			
<b>SECTION XIV - TRANSPORTATION INFORMATION</b>			
<b>DOT Shipping Name:</b> Not Regulated by DOT		<b>Canada TDG:</b> Not Regulated by TDG	
<b>DOT Hazard Class:</b>	n/a	<b>Hazard Class:</b>	n/a
<b>Identification #:</b>	n/a	<b>UN #:</b>	n/a
<b>SECTION XV - REGULATORY INFORMATION</b>			
<b>OSHA:</b>	This material is considered hazardous. See section 11.	<b>WHMIS:</b>	Serious eye damage/eye irritation - Category 2
<b>EINECS:</b>	Not Listed	<b>CND DSL:</b>	This product is listed on the DSL
<b>TSCA:</b>	This material is listed in the TSCA inventory and is not otherwise regulated by TSCA sec 4,5,6,7, or 12	<b>NTP:</b>	"Respirable crystalline silica, primarily quartz dust occurring in industrial and occupational settings, is know to be a human carcinogen."
<b>Calif Prop 65:</b>	Listed: Crystalline Silica (airborne particles of respirable size)	<b>RCRA:</b>	This material is not defined as hazardous waste

**SECTION XVI - OTHER INFORMATION**

PREPARED BY:	PHONE NUMBER	DATE
<b>Quality Control Staff, Absorbent Products Ltd.</b>	<b>1-800-667-0336</b>	<b>March, 2019</b>

All information presented herein is believed to be accurate; however, it is the user's responsibility to determine in advance of need that the information is current and suitable for their circumstances. No warranty or guarantee, expressed or implied is made by Absorbent Products Ltd., as to the information, or as to the safety, toxicity or the effect of this product.